

Operable Equipment

Note: Furnished equipment may vary for each unit and may not apply to your building.

Sliding Windows:

Tracks in sliding windows should be cleaned at regular intervals and drain holes must be kept open.

Sliding Doors:

Sliding door tracks and carriage trollies should be cleaned at regular intervals to prevent accumulation of dirt that might interfere with the door and cause premature wear of the trolley wheels. Do **NOT** use graphite spray to lubricate the door's overhead carriage wheels as it is a granular lubricant that will break down the movable parts. Instead, use Nylube <http://nylube.com/Lubes.html>

Make certain booth is level

Swing Doors:

Door hinges and Hydraulic Closer should be cleaned at regular intervals to prevent accumulation of dirt which might interfere with the door and cause premature wear of the door hardware. Make certain booth is level. Check and tighten hinge screws if necessary

Weather Stripping:

Door and window weather stripping should be checked at regular intervals for adjustment or damage.

Missing or damaged pieces should be replaced to seal unit against adverse weather conditions.

Light Fixtures:

Light fixtures equipped with acrylic lens should be cleaned regular interval to insure maximum light output.

Light fixtures containing two or more lamps should be replaced as a set.

Fan Forced Heater:

Refer to Heater Manufacturers instruction.

Periodically vacuum dirt and lint as required for safe and efficient operation.

Avoid using heater cabinets as a foot rest.

Do not put objects on or close to the heater, especially during operation.

Air Conditioner / HVAC Unit:

Refer to Heater Manufacturers instruction.

Periodically vacuum dirt and lint from grilles and clean filters as required for efficient operation.

Rest Room Fixtures:

Porcelain rest room fixtures may be cleaned with any over the counter rest room cleaner.